

### Type

PVAJP 711-1,2/1900

### Technical parameters:

Rated capacitance [uF]	C N	1900
Capacitance tolerance [%]		-10/+10
Rated voltage [V] DC	U N	1200
Insulating voltage [V]	U i	4 500
Rated current [A]	I max	160
Case temperature [°C]		-25/+70

### Limiting parameters:

Periodic peak voltage [V]	u max	1 350
Nonperiodic peak voltage [V]	u s	1 500
Repetitive peak current [kA]	i max	10 / 0,1 Hz
Maximum torque M 8		10 Nm

### Testing parameters:

Voltage test between terminals 1,5 x U N DC for time 10s  
Between terminals and case 2x U i + 1 000V AC for time 10 s


Self-healing system SH

Dry type

Weight 13 kg

Standard IEC 61071/91

Operating position arbitrary



OFFER

Dne :	11.7.2005
Kreslil :	Michalovičová
Konstruktér:	Ing.Lipenský Oldřich
Schválil :	

3BP 1139

564 22 ŽAMBERK, CZECH REPUBLIC, TEL.: 420/465 673 111, FAX: 420/465 612 319

E-MAIL: vyvoj@zez-silko.cz; obchod@zez-silko.cz

WEB SITE: www.zez-silko.cz