



Type:	<b>TKC1-12,5-134/400/525</b>	<b>A</b>	<b>B</b>	<b>C</b>	<b>D</b>	<b>E</b>	<b>F</b>	<b>H</b>				
Rated Voltage:	400V	180	135	180	100	108	7x14	M6				
Capacitor Power:	12,5kvar	DIMENSIONS [mm]										
Damping Coefficient p:	14%	<b>Notice:</b>										
Resonance Frequency:	134Hz	MODIFICATION										INDEX
Rated Frequency:	50Hz											
Inductance:	9,77mH											
Rated Current:	12,2A											
Capacitor Voltage:	525V											
Linearity:	≥ 1,38 In	<b>Drawn:</b>	Michalovičová				<b>Date:</b>	12.8.2014				
Losses:	55W	<b>Approved:</b>	Ing.Prokopec M.				<b>Date:</b>					
Weight:	11kg	<b>Drw. No.:</b>	<b>R-22-011-100</b>									
Winding Material:	Cu											



ZEZ SILKO s.r.o.  
Pod Černým lesem 683  
564 01 Žamberk  
Česká republika

tel.:  
fax.:  
email:  
http://

+420 465 673 111  
+420 465 612 319  
zez@zez-silko.cz  
www.zez-silko.cz